

Film stretch **REKORD**



REKORD

Rekord Technical Specs



► Designed for the most difficult conditions

Specifically designed and produced for the harshest conditions, with 12 month guarantee against UV.



► Excellent tack performance

The improved tack properties of the film ensure excellent bonding of the film layers, which creates better anaerobic conditions. Stretch films are specially designed for all high speed wrapping machines and for bales of increasing weight.



► Maximum resistance

Rekord (5 layers) and Rekord XL (7 layers) are extruded film with very high tack levels for superior performance.



Made from a special blend of resins to maximize puncture resistance.



► Oxygen barrier

Provide superior oxygen barrier properties to support the fermentation process.



Rekord and Rekord XL Films, respectively 25 μ - 5 layers and 22 μ - 7 layers, offering the complete solution for all silage needs in the field.

Perfect adhesion, excellent puncture resistance, Rekord and Rekord XL ensure perfect conservation of ensiled forage, promoting correct fermentation and preservation of the nutritional properties of the forage.

	Rekord		Rekord XL	
	500 mm	750 mm	500 mm	750 mm
Width (mm)	500 mm	750 mm	500 mm	750 mm
Polymer	100% UV stabilized LD polyethylene		100% UV stabilized LD polyethylene	
Roll Length (m)	1800 m	1500 m	2000 m	1650 m
Roll Diameter (mm)	260	240	260	240
Thickness	25 micron	25 micron	22 micron	22 micron
Color	green	green	green	green
Warranty	12 months	12 months	12 months	12 months
Rolls per pallet	48	20	48	20